

APPLICATION REVISIONS DASH ND. NEXT ASSY USED ON LTR DESCRIPTION DATE APPROVED Α 8/23/2006 INITIAL RELEASE A. Cash CONTR NO. ALL PAGES ARE OF ORIGINAL ISSUE (A) 100 Davids Drive, Hauppauge, New York 11788 8/23/2006 EXCEPT AS NOTED. PREP BY J. Mormile CHKD SPECIFICATION CONTROL A. Cash 10/26/2006 DRAWING PROJ ENGR Mormile 11/11/2006 Ka- BAND MIXER SIZE CODE IDENT. NO. APPROVAL (PROJ) А 33592 APPROVAL (GOVT) REV. 2 SCALE SHEET 1 DF



Marki Microwave P/N: M06169

Electrical Specifications

Input Frequency-

Band 1: 20.2-20.7 GHz Band 2: 20.7-21.2 GHz

LO Frequency-

Band 1: 12.95 GHz Band 2: 13.45 GHz

LO Drive: +8 to +13 dBm
Output Frequency: 7.25-7.75 GHz
Conversion Loss: 5.5 dB typical

6.5 dB maximum

Flatness: 0.5 dB/20.2-21.2 GHz

Isolation-

LO/RF: 25 dB typical LO/IF: 25 dB typical

Mechanical Specifications

Connectors-

LO: 2.92mm Female
RF: 2.92mm Female
IF: SMA Female

Outline Drawing: Marki Microwave Outline M06169

(MMITEQ	SIZE	code ident. No. 33592		170685	
Hauppauge, New York 11788	SCALE		REF.	SHEET 2 OF 2 REV.	Α